NEXORA™

Innovation that Builds the Future

STRONG BONDS. SMOOTH FINISHES.

Premium Tile Adhesive Solutions

Strong Bond | Smooth Finish | Water Resistant



PRODUCT CATALOGUE 2026

NEXORA™
Innovation that Builds the Future

CONSTRUCTION SOLUTIONS FOR A BRIGHTER TOMORROW



ABOUT US

Building Strong Bonds For The Future

With 15+ years of experience in the Indian market and 8+ years of export experience, Nexora brings proven expertise to the construction materials industry.

We offer a specialized range of Tile Adhesives, Tile Grouts, Epoxy Grouts, Block Joining Mortar, Wall Putty, and allied construction solutions, developed for strength, durability, easy application, and consistent performance.

15+
Years in Indian Market

8+
Years Export Experience

OUR PRODUCT RANGE

- Tile Adhesives
- Tile Grouts
- Epoxy Grouts
- Block Joining Mortar
- Wall Putty
- Allied Solutions

VISION

To become a trusted and globally recognized construction solutions brand, known for quality, innovation, reliability, and long-term performance.

MISSION

To deliver advanced and dependable construction solutions that meet evolving market requirements while maintaining high standards of product quality, manufacturing, and customer service.

WHY NEXORA

- QUALITY FOCUS
- RELIABLE PERFORMANCE
- EASY APPLICATION
- CUSTOMER COMMITMENT

NEXORA™
Innovation that Builds the Future



NEXO ECO

POLYMER MODIFIED TILE ADHESIVE

TYPE - I / C1 T

Ideal For Traditional Tiles, Ceramic Tiles And Porcelain Tiles.

PRODUCT DESCRIPTION

NEXO ECO is a cement-based tile adhesive formulated for reliable fixing of ceramic tiles with reduced vertical slip. Designed for smooth application and dependable bonding on properly prepared cementitious surfaces. Suitable for interior wall and floor applications in dry and wet areas.

RECOMMENDED APPLICATION

- TRADITIONAL TILES
- CERAMIC TILES
- INTERNAL USE ONLY
- RESIDENTIAL & COMMERCIAL USE

STANDARDS / SUITABILITY

CLASSIFIED AS	COMPLIMENT WITH
TYPE I	**C1 T**
IS 15477:2019	EN 12004-2017

KEY - BENIFITS

- HIGH BOND STRENGTH
- EASY APPLICATION
- ANTI SLIP
- FLEXIBLE POLYMER MODIFIED

COVERAGE*

Actual coverage of 1.2 kg/mm may vary depending on site and application conditions; coverage values are determined under standard laboratory conditions using a 6 × 6 × 6 mm notched trowel in accordance with IS 15477:2019.

PROPERTY	DETAILS
Product Type	Polymer Modified Tile Adhesive
Classification	Type I / C1 T
Apperance	Grey
Suitable Tiles	Traditional Tiles,Ceramic Tiles, Porcelain Tiles
Recommended Use	Internal Use
Pack Size	20 KG
Adhesive Thickness	2-10 mm
Walk-On Time	Light Walk: 24 Hours Heavy Walk : 3 days

NEXORA™
Innovation that Builds the Future



NEXO SMART

POLYMER MODIFIED TILE ADHESIVE

TYPE - II / C2 T

Ideal For Vitrified Tiles, Natural Stones & Tile-on-Tile Applications.

PRODUCT DESCRIPTION

NEXO SMART is a polymer-modified cement-based adhesive with high bond strength and excellent slip resistance. Designed for vitrified, porcelain, natural stone, and glass mosaic installations. Suitable for interior and exterior wall and floor applications

RECOMMENDED APPLICATION

- VITRIFIED TILES
- TILE ON TILE
- INTERNAL & EXTERNAL USE
- RESIDENTIAL & COMMERCIAL USE

STANDARDS / SUITABILITY

CLASSIFIED AS	COMPLIMENT WITH
TYPE II	**C2 T**
IS 15477:2019	EN 12004-2017

KEY - BENIFITS

- HIGH BOND STRENGTH
- EASY APPLICATION
- ANTI SLIP
- FLEXIBLE POLYMER MODIFIED

COVERAGE*

Actual coverage of 1.2 kg/mm may vary depending on site and application conditions; coverage values are determined under standard laboratory conditions using a 6 × 6 × 6 mm notched trowel in accordance with IS 15477:2019.

PROPERTY	DETAILS
Product Type	Polymer Modified Tile Adhesive
Classification	Type II / C2 T
Apperance	Grey Powder
Suitable Tiles	Vitrified Tiles ,Natural Stones, Tiles on Tiles
Recommended Use	Internal & External Use
Pack Size	20 KG
Adhesive Thickness	3-12 mm
Walk-On Time	Light Walk: 24 Hours Heavy Walk: 3 days

NEXORA™
Innovation that Builds the Future

NEXO FLEX

POLYMER MODIFIED TILE ADHESIVE

TYPE - III / C2 TE

Ideal For Vitrified Tiles, Natural Stones, Glass Mosaic



PRODUCT DESCRIPTION

Nexo Flex is highly Flexible, Multi-purpose, mineral adhesive for fixing Large Format Vitrified Tiles/ Natural Stone/ Glass Mosaic/ Italian Marble for Floor and wall application. Suitable for both internal and external areas.

RECOMMENDED APPLICATION

- VITRIFIED TILES
- GLASS MOSAIC
- INTERNAL & EXTERNAL USE
- RESIDENTIAL & COMMERCIAL USE

STANDARDS / SUITABILITY

CLASSIFIED AS	COMPLIMENT WITH
TYPE III	**C2 TE**
IS 15477:2019	EN 12004-2017

KEY - BENIFITS

- HIGH BOND STRENGTH
- EASY APPLICATION
- ANTI SLIP
- FLEXIBLE POLYMER MODIFIED

COVERAGE*

Actual coverage of 1.2 kg/mm may vary depending on site and application conditions; coverage values are determined under standard laboratory conditions using a 6 × 6 × 6 mm notched trowel in accordance with IS 15477:2019.

PROPERTY	DETAILS
Product Type	Polymer Modified Tile Adhesive
Classification	Type III / C2 TE
Apperance	Grey Powder
Suitable Tiles	Vitrified Tiles, Natural Stones, Glass Mosaic
Recommended Use	Internal & External Use
Pack Size	20 KG
Adhesive Thickness	3-15 mm
Walk-On Time	Light Walk: 24 Hours Heavy Walk : 3 days

NEXORA™
Innovation that Builds the Future



NEXO FLEX+

POLYMER MODIFIED TILE ADHESIVE

TYPE - III / C2 TES1

Ideal For Large Format Vitrified Tiles, Stone Cladding.

PRODUCT DESCRIPTION

Nexo Flex+ is highly polymer modified cement based adhesive with strong thixotropic property and high strength bonding for fixing large format Vitrified tile, Natural Stone, Glass Mosaic, Italian Marble for floor & wall application.Suitable for both internal and external applications.

RECOMMENDED APPLICATION

- VITRIFIED TILES
- STONE CLADDING
- INTERNAL & EXTERNAL USE
- RESIDENTIAL & COMMERCIAL USE

STANDARDS / SUITABILITY

CLASSIFIED AS	COMPLIMENT WITH
TYPE III	**C2 TES1**
IS 15477:2019	EN 12004-2017

KEY - BENIFITS

- HIGH BOND STRENGTH
- EASY APPLICATION
- ANTI SLIP
- FLEXIBLE POLYMER MODIFIED

COVERAGE*

Actual coverage of 1.2 kg/mm may vary depending on site and application conditions; coverage values are determined under standard laboratory conditions using a 6 × 6 × 6 mm notched trowel in accordance with IS 15477:2019.

PROPERTY	DETAILS
Product Type	Polymer Modified Tile Adhesive
Classification	Type III / C2 TES1
Apperance	Grey Powder
Suitable Tiles	Large Format Vitrified Tiles, Stone Cladding
Recommended Use	Internal & External Use
Pack Size	20 KG
Adhesive Thickness	3-18 mm
Walk-On Time	Light Walk: 24 Hours Heavy Walk : 3 days

NEXORA™
Innovation that Builds the Future

NEXO ULTRA

POLYMER MODIFIED TILE ADHESIVE

TYPE - IV / C2 TES1

Ideal For Full Body Tiles, Italian Marble



PRODUCT DESCRIPTION

Nexo Ultra is flexible highly polymer modified cement based adhesive with strong thixotropic property and high strength bonding for fixing large format Vitrified tile / Natural Stone / Indian Stone / Italian Marble for floor & wall application. Suitable for both internal and external applications.

RECOMMENDED APPLICATION

- VITRIFIED TILES
- ITALIAN MARBLE
- INTERNAL & EXTERNAL USE
- RESIDENTIAL & COMMERCIAL USE

STANDARDS / SUITABILITY

CLASSIFIED AS	COMPLIMENT WITH
TYPE IV	**C2 TES1**
IS 15477:2019	EN 12004-2017

KEY - BENIFITS

- HIGH BOND STRENGTH
- EASY APPLICATION
- ANTI SLIP
- FLEXIBLE POLYMER MODIFIED

COVERAGE*

Actual coverage of 1.2 kg/mm may vary depending on site and application conditions; coverage values are determined under standard laboratory conditions using a 6 × 6 × 6 mm notched trowel in accordance with IS 15477:2019.

PROPERTY	DETAILS
Product Type	Polymer Modified Tile Adhesive
Classification	Type IV / C2 TES1
Apperance	Grey Powder
Suitable Tiles	Full body Tiles, Italian Marble
Recommended Use	Internal & External Use
Pack Size	20 KG
Adhesive Thickness	3-18 mm
Walk-On Time	Light Walk: 24 Hours Heavy Walk : 3 days

NEXORA™
Innovation that Builds the Future



NEXO ADVANCE

POLYMER MODIFIED TILE ADHESIVE

TYPE - IV / C2 TES2

Ideal For Composite Marble, Stone, Quartz.

PRODUCT DESCRIPTION

NEXO ADVANCE is an advanced cement-based adhesive powered by geo-polymer technology for superior flexibility, high bond strength, and improved coverage*. Ideal for large-format tiles, vitrified tiles, Composite Marble, Stone, Quartz.

RECOMMENDED APPLICATION

- VITRIFIED TILES
- NATURAL STONE
- INTERNAL & EXTERNAL USE
- RESIDENTIAL & COMMERCIAL USE

STANDARDS / SUITABILITY

CLASSIFIED AS	COMPLIMENT WITH
TYPE IV	**C2 TES2**
IS 15477:2019	EN 12004-2017

KEY - BENIFITS

- HIGH BOND STRENGTH
- EASY APPLICATION
- ANTI SLIP
- FLEXIBLE POLYMER MODIFIED

COVERAGE*

Actual coverage of 1.2 kg/mm may vary depending on site and application conditions; coverage values are determined under standard laboratory conditions using a 6 × 6 × 6 mm notched trowel in accordance with IS 15477:2019.

PROPERTY	DETAILS
Product Type	Polymer Modified Tile Adhesive
Classification	Type IV / C2 TES2
Apperance	Grey Powder
Suitable Tiles	Composite Marble, Stone, Quartz
Recommended Use	Internal & External Use
Pack Size	20 KG
Adhesive Thickness	3-20 mm
Walk-On Time	Light Walk: 24 Hours Heavy Walk : 3 days

NEXORA™
Innovation that Builds the Future



NEXO EPOXY PRO+

PRODUCT DESCRIPTION

NEXO EPOXY PRO+ is a premium epoxy resin-based tile joint filler formulated to deliver exceptional stain and chemical resistance, superior water protection, and long-term durability. Its dense, non-porous and hard-wearing finish helps prevent moisture penetration and dirt absorption, creating smooth, hygienic joints that retain their appearance with minimal maintenance.

RECOMMENDED APPLICATION

- VITRIFIED TILES
- GLASS MOSAIC
- INTERNAL & EXTERNAL USE
- RESIDENTIAL & COMMERCIAL USE

STANDARDS / SUITABILITY

CLASSIFIED AS	CLASSIFIED AS
RG 1	**RG**
IS 17190-2020	EN 13888

KEY - BENIFITS

- STAIN, BACTERIAL & FUNGAL RESISTANT
- POLYMER-MODIFIED NON-SHRINK & WATER RESISTANT
- STRONG BOND
- EXTENSIVE COLOUR RANGE

ISO 9001:2015 | ISO 13007-1:2010 | IS 15477:2019

PROPERTY	DETAILS
Product Type	Resin(Part A) Hardner (Part B) Filler Powder (Part C)
Classification	RG 1/ RG
Apperance	Smooth Creamy Paste
Suitable Tiles	All Types Of Tiles And Glass Mosaic
Recommended Use	Internal & External Use
Pack Size	5 KG & 1 KG
Joint Width	3-22 mm
Walk-On Time	Light Walk: 24 Hours Heavy Walk : 3 days Swimming pool: More than 7 days

NEXORA™
Innovation that Builds the Future



NEXO SUPREME

PRODUCT DESCRIPTION

NEXO SUPREME is a high-performance, two-component reactive epoxy-polyurethane adhesive formulated for the installation of tiles, marble, and natural stone over a broad range of critical substrates. It provides high mechanical adhesion, excellent flexibility, dimensional stability, and superior resistance to moisture and thermal stress, ensuring long-term performance under demanding service conditions

RECOMMENDED APPLICATION

- VITRIFIED TILES
- NATURAL STONE
- INTERNAL & EXTERNAL USE
- RESIDENTIAL & COMMERCIAL USE

STANDARDS / SUITABILITY

CLASSIFIED AS **TYPE V 'T'S2** IS 15477:2019

CLASSIFIED AS **R2T** EN 12004-2017

KEY - BENIFITS

- SUPERIOR MULTI-SUBSTRATE ADHESION
- EXTREME ENVIRONMENTAL DURABILITY
- HIGH THERMAL STABILITY
- IMPACT & VIBRATION RESISTANCE
- DYNAMIC MOVEMENT ACCOMMODATION
- LONG-TERM WEATHERING RESISTANCE
- SUPERIOR CHEMICAL & STAIN RESISTANCE

PROPERTY	DETAILS
Product Type	Part A (Base) Part B (Hardner)
Classification	TYPE 5 'T'S2/ R2T
Apperance	Paste
Suitable Tiles	Any Tile
Recommended Use	Internal & External Use
Pack Size	5 KG & 1 KG
Grouting	After 24 Hours
Self Curing Time	7 Days
Walk-On Time	24 Hours

ISO 9001:2015 | ISO 13007-1:2010 | IS 15477:2019

NEXORA™
Innovation that Builds the Future



NEXO GROUT

PRODUCT DESCRIPTION

Nexo Grout is a premium-quality, high-performance, water-resistant cement-based tile grout designed for filling and sealing tile joints. Suitable for ceramic, vitrified, porcelain, and natural stone tiles, it provides a smooth, uniform, and aesthetically appealing finish. Its advanced formulation ensures excellent adhesion, durability, abrasion resistance, and crack resistance while preventing dust formation.

RECOMMENDED APPLICATION

- VITRIFIED TILES
- GLASS MOSAIC
- INTERNAL & EXTERNAL USE
- RESIDENTIAL & COMMERCIAL USE

KEY - BENIFITS

- HIGH BOND STRENGTH
- EASY APPLICATION
- WATER RESISTANT
- SMOOTH & UNIFORM FINISH
- ABRASION RESISTANT
- CRACK & SHRINKAGE RESISTANT

COVERAGE

Please refer to the Technical Data Sheet (TDS) for detailed technical parameters and application instructions.

PROPERTY	DETAILS
Product Type	Cementitious Powder
Classification	CG2WA
Apperance	Powder
Suitable Tiles	Any Tile
Recommended Use	Internal & External Use
Pack Size	1 KG
Thickness	0 to 3 mm
Walk-On Time	24 Hours

NEXORA™
Innovation that Builds the Future

BUILT ON TRUST FOR A BETTER TOMORROW

TILES ADHESIVES
THAT CREATE
LASTING SPACES



WE ARE ALWAYS HERE FOR YOU

CONTACT US

Let's Build Stronger Spaces Together

"SOLUTIONS
FOR TODAY
FOUNDATIONS
FOR TOMORROW"

VISIT US
Nexora Global Industries Pvt.Ltd.
Shade no. 2, Survey no. - 1525/119,
Near Navkar Heights, Off S.P. Ring Road,
Ognaj, Ahmedabad - 380060

CALL US
+91 92748 58900
+91 92748 28900
+91 92748 28901

EMAIL US
info@nexoraindia.org
sales@nexoraindia.org

WEBSITE
www.nexoraindia.org

- PRODUCTION INQUIRIES
- TECHNICAL SUPPORT
- DEALERSHIP OPPORTUNITIES
- EXPORT INQUIRIES



NEXORA GLOBAL INDUSTRIES PVT.LTD.